North American Electric

PE444T-75-8C

GENERAL PURPOSE ELECTRIC MOTOR
NEMA PREMIUM EFFICIENCY
TOTALLY ENCLOSED FAN COOLED
INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31
Factory Certified for T2B Class I, Division II, Groups A,B,C & D and Class II, Division II, Groups F & G



DIMENSIONS

HP	RPM	Frame	MOUNTING														
			A	B	C	D	G	H	J	E	2E	2F1	2F2	O	P	T	BA
75	900	444T	21.7	22.9	44.3	11	1.35	0.81	3.35	9	18	14.5	16.5	22.1	21.6	3	7.5

Shaft Extension, Key Set						Conduit Box		Bearings		Mount
U	V	R	S	ES	N-W	AA	AB	DE	ODE	
3.375	8.25	2.88	0.875	6.91	8.5	3	19	NU319	6318	F1

BEARING LUBRICATION: The bearings come lubricated with Mobil Polyrex EM Polyurea Grease. It is recommended that you add some additional lubrication when the motor is installed.
Three options (brands) for suitable lubrication include, but are not limited to, the following:
1.) Mobil Polyrex EM
2.) Citco Polyurea MP
3.) Conoco Phillips Polytac EP

ISO9001 CERTIFIED CE NEMA Premium C SA US

PO Box 130 350 Vaiden Drive Hernando, MS 38632-0130
Phone: 662-429-8049 Fax: 662-429-8546 Toll Free: 800-884-0404 www.naemotors.com

North American Electric

PE444T-75-8C

GENERAL PURPOSE ELECTRIC MOTOR
NEMA PREMIUM EFFICIENCY
TOTALLY ENCLOSED FAN COOLED
INVERTER DUTY 10:1 CT; 20:1 VT - NEMA MG1 PART 31
Factory Certified for T2B Class I, Division II, Groups A,B,C & D and Class II, Division II, Groups F & G

PERFORMANCE DATA

HP	RPM	Frame	Voltage	Frequency (Hz)	Full Load S.F.	Insulation Class	NEMA Design	Slip (%)	NEMA Code	Enclosure Type	IP Rating	Max. Ambient
75	885	444T	230/460	60	1.15	F	C	1.7	G	TEFC	55	40 °C

Amps (460V)		Efficiency (%)			Power Factor			Torque (ft-lb)			DE Bearing	ODE Bearing	Connection	Weight (lbs.)
FLA	LRA	100%	75%	50%	100%	75%	50%	FLT	LRT %	BDT %				
95	542	93.6	93.6	92.5	0.80	0.72	0.60	445	200	240	NU319	6318	12 Lead 2Δ/Δ	1353

**Usable at 208 Volts*

NAME PLATE

North American Electric

AC INDUCTION MOTOR
INVERTER DUTY 20:1 VT; 10:1 CT

NEMA Premium

CAT NO. PE444T-75-8C			FRAME 444T		PHASE 3
HZ 60	S.F. 1.15	HZ 50	S.F. 1.0	ENCL TEFC	IP 55
HP 75	RPM 885	HP 75	RPM 740	DUTY CONT	DES C
VOLTS 230/460		VOLTS 190/380		AMB 40 °C	INS F
AMPS 190 / 95		AMPS 230/115		DE BRG NU319	
CODE G	P.F. 0.80	CODE F	P.F. 0.82	ODE BRG 6318	
EFF 93.6	MIN 92.4	EFF 92.0	MIN 90.5	LUB: Mobil Polyrex EM	
MOTOR WEIGHT 1353 LBS		CONNECTION 12 Lead 2Δ/Δ		SER NO	

General purpose use on industrial machinery installed in damp, dusty or dirty environments.

Hernando, Mississippi

ISO9001 CERTIFIED

CE

C SP US 272709

CC082A

CONNECTION DIAGRAMS

230V



460V



APPLICATIONS:

General purpose use on pumps, fans, blowers, compressors, conveyors, material handling and other industrial machinery installed in damp, dusty or dirty environments.

PO Box 130 350 Vaiden Drive Hernando, MS 38632-0130
Phone: 662-429-8049 Fax: 662-429-8546 Toll Free: 800-884-0404 www.naemotors.com